

Pneumatic stripping machine

PS 3.2

Benchtop pneumatic stripping machine for wires from 0,03 to 2 mm²



Technical specifications are subject to change according to possible needs and without notice.

FEATURES

- Pneumatic wire stripper for stripping single-core wires with cross-sections from 0,03 to 2 mm² and diameters up to 3,2 mm
- No blades change necessary
- Extremely fast cycle time
- The machine is equipped with a safety cover
- Suitable for stripping wires and inner cable conductors
- Simple and intuitive operation
- Absolute precision and high process repeatability
- Compact design
- Possibility of total or partial stripping

TECHNICAL SPECIFICATIONS

	PS 3.2
Cross section	0,03 - 2 mm ² (32 - 14 AWG)
Precision of diameter setting	max 3,2 mm
Outer cable diameter	0,01 mm
Strip length	1 - 20 mm
Full strip increments	0,5 mm
Partial strip increments	2 mm
Cycle time	approx. 0,3 sec
Start cycle	sensor
Stripping blade	V - blades
Noise level	< 75 db (A)
Air supply	5 - 7 bar
Dimensions & Weight	290 x 64 x 125 mm / 2 kg

CE Conformity: PS 3.2 is fully compliant with CE regulations and EMC equipment guidelines for mechanical, electrical and electromagnetic compatibility.

Note: we recommend to send samples with the application requirements for a preliminary examination.

